

## OEM Trackballs

### GK/GS Series Trackballs

#### FEATURES

- Keyboard or panel mount
- PS/2 Output
- USB Output
- Phase Quadrature Output
- Vandal proof versions



The GK Series of trackballs are ruggedised professional trackballs for harsh industrial environments. The double-sided seal ring provides a sealing to IP65 static (ball at rest). Stainless Steel shafts and bearings ensure a solid and precise pointer control. The units can be used for front panel mounting (remove the mounting bracket) or for back panel mounting.

The GK Series of trackball diameters range from 16mm to 75mm.

The GS Series of trackballs are ruggedised professional trackballs for vandal proof applications. The ball and top flange are made of quality Stainless Steel. The double-sided seal ring provides a sealing to IP65 static (ball at rest). Stainless Steel shafts and bearings ensure a solid and precise pointer control.

The units can be used for front panel mounting (remove the mounting bracket) or for back panel mounting.

The GS Series of trackball diameters range from 38m to 50mm.

#### GK Series Trackballs

Part Number	Ball Diameter	Output
GK16-1502	16mm	PS/2
GK25-4502	25mm	PS/2
GK25-4602	25mm	USB
GK25-4002	25mm	Phase Quadrature
GK38-4502	38mm	PS/2
GK38-4602	38mm	USB
GK38-4002	38mm	Phase Quadrature
GK50-4502	50mm	PS/2
GK50-4602	50mm	USB
GK50-4002	50mm	Phase Quadrature
GK75-1502	75mm	PS/2
GK75-1602	75mm	USB

#### GS Series Trackballs

Part Number	Ball Diameter	Output
GS38-4502	38mm	PS/2
GS38-4602	38mm	USB
GS38-4002	38mm	Phase Quadrature
GS50-4502	50mm	PS/2
GS50-4602	50mm	USB
GS50-4002	50mm	Phase Quadrature