

**I-SFT  
160i.15X**

15.0" XGA High Brightness  
Active Matrix LCD Display



**FEATURES**

- The 15" I-SFT 160i.15X offers XGA (1024 x 768 dots) resolution and wide viewing angles
- Integrated Inverter
- 1600 cd/m2 Backlight Brightness
- Extended Temperature Range
- Long Life CCFL

Display Mode	Transmissive Mode, Normally White
Display Format	1024 (x3) x 768 Pixels
Screen Area	308.0 x 229.80.4mm (15 inch diagonal)
Display Outline	354.0 (H) x 264.0 (V) x 25.7 (D) mm (Typ.)
Contrast Ratio	350:1 (Typ.)
Brightness	1600 cd/m2
Viewing angle	+/- 70° horizontal, 50°/-55° vertical
Dimming	1:1000
MTTH	>50,000 Hours
Shock (operating)	35g; 6ms
Vibration (operating)	3g; 10 to 2000Hz
Temperature (operating)	-10°C to +60°C
Temperature (storage)	-25°C to +70°C
Weight	2.55 Kg
Input Signal	TTL, 2 pixel
Power Consumption	43 Watt (Typ.)
Power Supply	24 VDC int. inverter, 5V LCD
Response Time	45 ms (Typ.)