

I-SFT 75i

10.5" VGA High Brightness
Active Matrix LCD Display



FEATURES

- The 10.5" I-SFT 75i offers VGA (640 x 480 dots) resolution and wide viewing angles
- Integrated Inverter
- 720 cd/m² Backlight Brightness
- Extended Temperature Range
- Long Life CCFL

| | |
|-------------------------|--|
| Display Mode | Transmissive Mode, Normally White |
| Display Format | 640 (x3) x 480 Pixels |
| Screen Area | 211.2 x 158.4mm (10.5 inch diagonal) |
| Display Outline | 271.0 (H) x 192 (V) x 27.0 (D) mm (Typ.) |
| Contrast Ratio | 400:1 (Typ.) |
| Brightness | 720 cd/m ² |
| Viewing angle | +/- 80° horizontal, 45°/-80° vertical |
| Dimming | 1:250 |
| MTTH | 50,000 Hours |
| Shock (operating) | 100g; 11ms |
| Vibration (operating) | 3g; 5 to 150Hz |
| Temperature (operating) | -25°C to +85°C |
| Temperature (storage) | -35°C to +85°C |
| Weight | 1.22 Kg |
| Input Signal | 6-bit RGB |
| Power Consumption | 20 Watt (Typ.) |
| Power Supply | 12 VDC |
| Response Time | 40 ms (Typ.) |