

25mm Trackballs
Stainless Steel
Vandalproof

FEATURES

- **IP65 Rating (ball at rest)**
- **Stainless Steel carrier plate**
- **Two Stainless Steel sealed switches**
- **PS/2 or USB compatible**



TBS25F2



SBS25F2

General Description

This range uses the compact 25mm industrial grade trackball with black phenolic ball or with stainless steel ball. The units feature a stainless steel carrier plate, a stainless steel top flange protecting the trackball sealing, two stainless steel sealed switches and a silicone gasket that seals the unit into the panel. These trackballs are Vandalproof.

SPECIFICATIONS

Carrier Plate: Brushed Stainless Steel
Ball diameter: 25mm
Ball material: Phenolic Resin with metal core or Stainless steel
Tracking Force: 50 grams nom. (TBS25F2)
 65 grams nom. (SBS25F2)
Operating Temperature: 0°C to +55°C
Storage Temperature: -25°C to +85°C
Lifetime: > 2 million ball revolutions
Sealing: IP65 static

Push Button Switches:

Sealing: IP65
Travel: 1.3mm
Operating Force: 4N typ.
Mechanical Life: 1 million operations
Contacts: Gold plated

ORDERING INFORMATION

Phenolic Resin Ball	Stainless Steel Ball
TBS25F2	SBS25F2

PS/2, USB Combo